

IP-8m

Audio over IP codec

Professional multi-format multi-channel audio encoder / decoder



IP-8m Audio over IP codec 1/2



Audio networks based on different protocols

- ▶ Broadcast based on EBU TECH 3326, SMPTE ST 2110
- ▶ AES67 based on RAVENNA, Livewire or Dante

Audio coding – fitting to your needs

High quality multi-channel audio de- / encoding

- ▶ Phase-locked audio for surround applications
 - PCM
 - E-aptX
 - AAC
 - Dolby Digital Plus AC3/E-AC3 (option)
- ▶ MPEG ½ Layer 2, 3
- ▶ G.711, G.722, Linear PCM
- ▶ Opus
- ▶ MPEG 2/4 AAC LC
- ▶ MPEG 4 AAC LD/ELD/ELdv2
- ▶ MPEG 4 HE-AAC v1&v2
- ▶ Extended HE-AAC (xHE-AAC)
- ▶ Enhanced aptX (E-aptX)
- ▶ Optional: Bit transparent transmission of digital audio

IP streaming (unicast, multiple unicast & multicast)

Rock solid network connection even in stress conditions according to standards RFC 3550, RFC 3551, RFC 3640, RFC 2250

- ▶ Professional audio IP streaming using UDP, RTP and SIP/SDP (standardized by EBU N/ACIP Tech 3326)
- ▶ TS RTP, UDP and SRT streaming
- ▶ SRT Secure Reliable Transport
- ▶ PRO MPEG FEC, Dual streaming
- ▶ Optional: Livewire/ Ravenna (SIP, SAP, RTSP, PTPv2)
- ▶ HLS, Icecast source client

Backup / advanced redundancy management

- ▶ Flexible automatic switch over concept with free definition of alternative input sources as redundancy solution in case of failures
- ▶ Playing files from internal storage or using alternative streams (Icecast / Shoutcast)
- ▶ Dual IP ports for data + 1 IP port for control interface
- ▶ Optional: redundant power supply 230 VAC or 48 VDC

Control

- ▶ Remote control with various possibilities: HTTP/S, FTP, Telnet, NMS, SNMP v2c
- ▶ Revised configuration via web user interface for easier setup
- ▶ Insertion of localized advertisement
- ▶ Relays, inputs
- ▶ Ember+

Special

- ▶ Energy efficient DSP based 24/7 broadcast quality
- ▶ Embedded auxiliary data (RBDS/RDS or PAD) and GPIO forwarding
- ▶ Optional: Perfect network synchronization for SFN applications

Monitoring

- ▶ Headphone output
- ▶ Icecast Live Listening



IP-8m – Audio over IP codec 2/2

IP-4c
Name: IP-4c Testdevice
Location: 2wcom Systems
Description:

Power Warning
Input Output

Live Source: Audio Output 1

Codec

Input Sources / Profiles

Name	Address	Interface	Delay	FEC ports	Codec	Buffer	Ancillary	Clock
Default	@:5004	Data 1	100	--	Auto	100	--	Internal
Default	@:6004	Data 1	100	--	Auto	100	--	Internal

Encoder Decoder

Source Assignment

	Main	Backup 1	Backup 2	Backup 3
Audio 1	<input checked="" type="checkbox"/> ON Default @:5004	<input checked="" type="checkbox"/> ON NDR 2 SH www.ndr.de/.../ndr2_sh.m3u	<input type="checkbox"/> OFF None	<input type="checkbox"/> OFF None

Advanced control functionalities

High quality multi-format audio de-/encoding:

- ▶ HTTP/HTTPS: via web interface
- ▶ FTP: XML file control
- ▶ NMS: Control via centralized Network Management System

Highly sophisticated monitoring and alarm concept

- ▶ Adjustable silence detection
- ▶ IP buffer and jitter check
- ▶ PLL control
- ▶ SNMP, alarm, source switch & event logging

Perfect audio quality

- ▶ Balanced digital AES/EBU (integrated XLR connector)

Advanced IP robustness functionalities

- ▶ Even to operate in standard IP networks
- ▶ PRO MPEG FEC
- ▶ Management of packet size, buffer and QoS
- ▶ Optional: Stream4Sure – 2wcom streaming technology with different codes / qualities and seamless switching of up to 4 streams

Perfect audio & latency management

- ▶ Optional: GPS based 2wcom latency control solution usage in SFN FM networks
- ▶ ACIP compliant high audio quality and extremely low latency (PTPv2 network synchronization)



Technical details 1/2



Audio (encoder / decoder)

Codexs

Standard	MPEG 1/2 Layer 2, 3 Linear PCM G.711, G.722 Opus MPEG 2/4 AAC LC MPEG 4 AAC LD/ELD/ELD v2 MPEG 4 HE-AAC v1&v2 Extended HE-AAC (xHE-AAC) Enhanced aptX (E-aptX)
On request / roadmap	Dolby Digital (AC3) Dolby Digital Plus (E-AC3) Ask for other codexs
On request	Bit transparent transmission of AES/EBU input
Sample rates	kHz: 48 (On request: up to 192 kHz)

Interfaces

Performance

Digital (in/out)	4x AES/EBU, 110 Ω bal., integrated XLR
Analog (in)	2x L/R, > 10 Ω bal., integrated XLR
Analog (out)	2x L/R, < 20 Ω bal., integrated XLR
Headphone (out)	L/R, < 10 Ω, 6,3 mm
Digital reference input	No dedicated input, selectable by user
Digital reference level	9 dBFS (adjustable)
Gain	-9....+6 dB

Dynamic range

16 Bit, > 89 dB
24 Bit, > 130 dB

Frequency response

Depends on sample rate – e.g. 48 kHz: 0,1 dB; 20 Hz ... 22,5 kHz

Phase locking

2-8 Mono channels can be phase locked to provide up to 7.1 surround sound

Ethernet

Data

Audio, serial data and GPIO transmission, controlling and setup functions

Connector Type

3x RJ45
Auto switching 10/100/1000 BASE-T

Protocol

RTP/RTCP/UDP, SRT Secure Reliable Transport, IGMP, ICMP, DHCP, HTTPS, SFTP, SNMP, NTP, TCP (Icecast), HLS, PTPv2, SMTP ST 2110

Serial

Interface

8x RS-232C Sub D-15

Data

Private data, MPEG ancillary data, UECP/RDS (acc.to TR 101 154)

Transmission rate

1200 to 115200 baud, asynchronous

USB

1x USB 2.0 interface for service



Technical details 2/2

Interfaces

Contact closure

Inputs	8x 26 pole sub-D female
Outputs	7+1 floating relays 7 relays SPST (from A) 2 relays SPDT (from C) DC: max. 30 V, 1 A, 10 W 26 pole sub-D male

Internal storage

Data	internal audio files
Size	7 GB (optional 1000 GB)
Type	eMMC (optional SSD)

Time synchronization (optional)

PTPv2	Network synchronization according to IEEE 1588-2008
1PPS	SMA connector

Control & monitor

Ethernet

User interface	Integrated WebGUI, LCD display
Data	Control and setup functions
USB	USB 2.0 interface for service, configuration and firmware updates
Protocol	2wcom NMS, Telnet, HTTPS, SNMP, UDP, RTCP, SRT Secure Reliable Transport, SFTP, IGMP, ICMP, NTP, DHCP, SNMP, SSH, PTPv2, TCP (Icecast)

Front panel

LCDisplay	Graphical, 264x64 pixel
Jog wheel	Impulse, enter button
4 Duo LEDs	Power, input, output, warning

General data

Power consumption	<20W
Case dimensions	19", 1 HU, Depth: 310 mm, Width: 424 mm, Front panel: 484 mm
Weight	< 5 kg
Material	Steel plate (aluminium-zinc coated)
Operating temp. range	0...+45°C
Storage temp. range	-40...+70°C
Languages	English

Power supply

Standard	1x internal, 90...260 VAC, 47...63 Hz, 1x power port (rubber connector)
Optional version 1	Two internal redundant power supplies (230 VAC or 48 VDC), aut. switchover
Optional version 2	Two external hot swappable redundant power supplies (230 VAC or 48 VDC), aut. switchover